

ALPHA PRIM



Series ALPHAPRIM



Models



Alpha 1



Alpha 2



Alpha 3



Alpha 4



Alpha 5



Alpha 6



Alpha 7



Certified according to EN 14450 Security level S1

- ⊙ Single-walled body throughout with the anti-drill-protection.
- ⊙ Double-walled door: total thickness 56 mm.
- ⊙ Three-way locking mechanism with round solid bolts with a diameter of 20 mm.
- ⊙ Standard preparation for floor anchoring, incl. certified anchoring material.
- ⊙ Shelves are adjustable to every 30 mm.
- ⊙ Internal hinges – Door opening angle 102°.
- ⊙ Optimal File capacity. File acc. to DIN 821-D1-80 ($w_1=75$ mm).

⊙ Measurements

ALPHAPRIM

MODEL	* External dimensions			Internal dimensions			Weight	Volume	Max. No. of Files
	Height [mm]	Width [mm]	Depth [mm]	Height [mm]	Width [mm]	Depth [mm]	Approx. [kg]	Approx. [liters]	
Alpha 1	340	326	244	287	320	185	19	17	-
Alpha 2	340	446	364	287	430	305	30	38	1+
Alpha 3	430	446	364	377	430	305	35	49	5
Alpha 4	550	446	364	497	430	305	42	65	5+
Alpha 5	790	496	364	737	480	305	59	108	12
Alpha 6	1150	496	364	1097	480	305	80	161	18
Alpha 7	1510	496	364	1457	480	305	101	213	24



Locking according to EN 1300 Grade A:

- 1 mechanical key lock or
- 1 electronic lock Code Combi K.

