

STARPRIM



Models



4080/N



4095/N



4175/N



4215/N



4285/N




4395/N




4440/N



4535



4780



4EX

**Certified according to EN 1143-1
Security Grade IV**

- ⊙ Three-way locking mechanism with solid-steel bolts with a diameter of 40 mm, except models 4535 and 4780 – four way locking mechanism.
- ⊙ A continuous formed dog bar on the hinge side protects the safe in event of attack.
- ⊙ The door-frame is equipped with fire-resistant washer which protects safe interior against dust and direct irruption of flame, smoke and gases.
- ⊙ All safe models are able to be secured to a floor. Also provision for snap-off detector is installed.
- ⊙ Shelves are adjustable to every 50 mm, except models 4535 and 4780 – adjustable shelves to every 25 mm.
- ⊙ The hinges enable 205° door opening for full access.
- ⊙ Optimal File capacity. File acc. to DIN 821-D1-80 ($w_1=75$ mm).

⊙ **Measurements**

STARPRIM

| MODEL | * External dimensions | | | Internal dimensions | | | Weight | Volume | Max. No. of Files |
|-----------------|-----------------------|------------|------------|---------------------|------------|------------|--------------|------------------|-------------------|
| | Height [mm] | Width [mm] | Depth [mm] | Height [mm] | Width [mm] | Depth [mm] | Approx. [kg] | Approx. [liters] | |
| 4080/N | 600 | 610 | 464 | 509 | 530 | 305 | 315 | 82 | 7 |
| 4095/N | 785 | 535 | 464 | 694 | 455 | 305 | 355 | 96 | 12 |
| 4175/N | 955 | 610 | 544 | 864 | 530 | 385 | 495 | 176 | 14 |
| 4215/N | 1135 | 610 | 544 | 1044 | 530 | 385 | 565 | 213 | 21 |
| 4285/N | 1490 | 610 | 544 | 1399 | 530 | 385 | 675 | 285 | 28 |
| 4395/N | 1490 | 760 | 574 | 1399 | 680 | 415 | 845 | 395 | 36 |
| 4440/N | 1315 | 760 | 689 | 1224 | 680 | 530 | 875 | 441 | 27 |
| 4535 | 1850 | 840 | 580 | 1720 | 730 | 415 | 1165 | 521 | 45 |
| **4780 | 1850 | 1190 | 580 | 1720 | 1080 | 415 | 1450 | 771 | 70 |
| EX 4-889 | 889 | 470 | 725 | 809 | 364 | 566 | 523 | 167 | |

* – 45 mm extra depth with handle and different locks.

** – Double doors.

- Standard locking: 1 mechanical key lock according to EN 1300 Grade B and 1 mechanical combination lock according to EN 1300 Grade B.
- Optional locks, inside equipment and additional equipment are evident from special STARPRIM Specification.

